

Schwing 61 SX Specifications

Pump Kit on S 58 SX / S 61 SX

2525H-6 120/85 MPS

| | U.S. | Metric |
|--|------|--------|
| Theor. Concrete Output Per Hour (cubic yards - cubic meters) | 213 | 163 |
| Maximum Pressure on Concrete (psi - bar) | 1169 | 80 |
| Maximum Strokes Per Minute | 22 | |
| Material Cylinder Diameter (in. - mm) | 10 | 254 |
| Material Cylinder Stroke Length (in. - mm) | 98 | 2500 |
| Differential Cylinder Diameter (in. - mm) | 4.7 | 120 |
| Maximum Aggregate Size (in. - mm) | 2.5 | 63.5 |

Boom Specifications

S 58 SX / S 61 SX

| | U.S. | Metric |
|-----------------------------------|---------------|-------------|
| Pipeline Diameter(in. - mm) | 5 / 4.5 | 125 / 112 |
| Vertical Reach(ft.-in. - m) | 187-9 / 197-1 | 57.2 / 60.1 |
| Horizontal Reach(ft.-in.- m) | 175-2 / 184-6 | 53.4 / 56.1 |
| Net Horizontal Reach(ft.-in. - m) | 162-6 / 171-9 | 49.5 / 52.3 |
| Unfolding Height(ft.-in. - m) | 56-5 / 59-8 | 17.2 / 18.2 |
| Section Lengths | | |
| First Section(ft.-in. - m) | 34 / 34 | 10.4 / 10.4 |
| Second Section(ft.-in. - m) | 49 / 49 | 15 / 15 |
| Third Section(ft.-in. - m) | 47-3 / 50-8 | 14.4 / 15.4 |
| Tip Section(ft.-in. - m) | 44-10 / 50-8 | 13.6 / 15.4 |
| Slewing Range (degrees) | 380° / 380° | |
| End hose length(ft. - m) | 12 / 10 | 3.6 / 3 |

Specifications are subject to change without prior notice.

EASy One Sided Outrigging System

